



APPLICATION GUIDE

This application guide contains the steps for all Smarter Surfaces projector paint products. These include:

- **Smart Projector Paint Pro**
- **Smart Projector Paint**
- **Smart Projector Paint Contrast**

All Projector Paint products are suitable for use on plaster, wallboards, wood, metal and concrete. For interior use only.

Please read the section that is relevant to your application.

HOW TO APPLY SMART PROJECTOR PAINT AND SMART PROJECTOR PAINT PRO

Smart Projector Paints are extremely high quality projection paints that enable users to project the clearest images possible. They come in a white finish and are designed to be used with projection equipment.

Each tin covers an area of 6m² / 64 sq. ft.

1

PREPARE THE SURFACE

- All surfaces to be painted should be clean, dry and free from loose materials.
- Measure the area you wish to paint and clearly mark it using masking tape.
- Prime bare, untreated surfaces with **Smart White Primer**.
- Once primed, lightly sand the surface.

2

APPLY THE PROJECTOR PAINT

- Stir paint thoroughly before use.
- For best results, apply paint using a foam or a mohair roller.
- Apply 2 coats allowing first coat to dry before applying the second coat (approx. 2 hours).

3

DRYING TIME

- Smart Projector Paint will be touch-dry in 1 hour and usable after 24 hours.

HOW TO APPLY SMART PROJECTOR PAINT CONTRAST

Smart Projector Paint Contrast is a two-part projection paint that comes in a gray finish and covers an area of 6m² / 64 sq. ft. This product is designed to be used with most projectors.

1

PREPARE THE SURFACE

- All surfaces to be painted should be clean, dry and free from loose materials.
- Measure the area you wish to paint and clearly mark it using masking tape.
- Prime bare, untreated surfaces with **Smart White Primer**.
- Once primed, lightly sand the surface.

2

APPLY THE BASECOAT OF PROJECTOR PAINT

- Stir paint thoroughly before use. If applying your paint to new plaster work, thin the paint up to 20%.
- For best results, apply paint using a foam roller.

Base Coat

- Apply your first coat of the base coat tin.
- Sand smooth when dry and then add the second coat.
- Wait for paint to fully dry before adding Smart Projector Paint Contrast top coat.

Top Coat

- Ensure base coat is smooth and free from surface defects.
- Apply first coat with a foam roller. Allow to dry before applying second coat.

3

DRYING TIME

- Once all coats are applied Smart Projector Paint Contrast will be ready to use in 24 hours.

Product Liability Clause

The sale of our products is subject to our General Terms and Conditions available on www.smartersurfaces.com



Support:

Email:
support@smartersurfaces.com

Website:
www.smartersurfaces.com