

SMART OUTDOOR PROJECTOR SCREEN PAINT

APPLICATION GUIDE

Smart Outdoor Projector Screen Paint is suitable for use on exterior surfaces such as plaster, mortar, brick, stone, metal cladding, aluminium and composites. For Exterior use.

There are two kits available:

4.5m² / 48 sq. ft.

This will create a screen size of: 120" or 279cm x 157cm (109.8" x 61.8") - at aspect ratio 16:9

Or

13.5m² / 144 sq. ft.

This will create a screen size of: 220" or 487cm x 274cm (191.73" x 107.87") - at aspect ratio 16:9

HOW TO APPLY SMART OUTDOOR PROJECTOR SCREEN PAINT

1 PREPARE THE SURFACE

- Surfaces that have been exposed to the elements for some time should be washed clean with waterjet or similar method.
- Scrap and sand any rough masonry
- Measure the area you wish to paint ensuring you have enough paint to cover this area.
- Apply one coat of Smart White Primer before the projector paint.

For new surfaces such as plaster or mortar paint apply two coats of white exterior wall paint before applying the primer coat.

2 APPLY THE SMART OUTDOOR PROJECTOR SCREEN PAINT

- Stir paint thoroughly before use.
- For best results, apply paint using a short pile roller sleeve.
- Apply 2 coats allowing the first coat to dry before applying the second coat (approx. 2-4 hours at 20°).

3 DRYING TIME

- Smart Outdoor Projector Screen Paint will be touch-dry in 1 hour and usable after 12 hours.

PRODUCT LIABILITY CLAUSE

The sale of our products is subject to our General Terms and Conditions available on www.smartersurfaces.com

SUPPORT

EMAIL:
support@smartersurfaces.com

PHONE (IRE):
+353 1 412 6200

WEBSITE:
www.smartersurfaces.com