



SMART CHALKBOARD PAINT

APPLICATION GUIDE

HOW TO APPLY SMART CHALKBOARD PAINT

Smart Chalkboard Paint is suitable for use on plaster, wallboards, wood, metal and concrete. Each tin covers up to 6 s.q.metres/ 65 s.q. feet (based on 2 coats). For interior use only.

1 MEASURE YOUR AREA

- Measure the area accurately ensuring you have enough paint.

2 PREPARE THE SURFACE

- All surfaces to be painted should be clean, dry and free from loose materials.
- Clearly mark the area you wish to paint using masking tape.
- Prime bare, untreated surfaces with **Smart White Primer**.
- Once primed, lightly sand the surface.

3 HOW TO APPLY CHALKBOARD PAINT

- Stir paint thoroughly before use.
- For best results, apply paint using a foam roller.
- Paint the surface using light even strokes, covering 1 metre sections at a time.
- Apply 2 coats allowing first coat to dry before applying the second coat (approx. 2 hours).

4 DRYING TIME

- Smart Chalkboard Paint will be touch-dry in 1 hour and usable after 24 hours.

5 PREPARATION BEFORE USE

- Before writing on the surface for the first time, condition the surface by rubbing the side of a stick of chalk all over the surface and erasing immediately with a dry cloth or eraser.

6 ONGOING CLEANING


- Your chalkboard surface can be cleaned with a **micro-fibre eraser cloth**.
- A chalky residue will remain when cleaning with a dry cloth or eraser. This can be removed by using a damp cloth.

PRODUCT LIABILITY CLAUSE

The sale of our products is subject to our General Terms and Conditions available on www.smartersurfaces.com

SUPPORT

 EMAIL:
support@smartersurfaces.com

 PHONE (IRE):
+353 1 412 6200

 WEBSITE:
www.smartersurfaces.com